RoHS Compliant

MRUSB-5B-ED8x-S347

SHELL鍍層:

TN
NI





P.C.B LAYOUT MOUNTING PATTERN

NOTES:

MATERIAL:

1.1 HOUSING: LCP

1.2 CONTACT: PHOSPHOR BRONZE

1.3 SHELL: BRASS

Finish:

2.1 Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls
Nickel under plated overall

3.SPECIFICATION:

3.1 CURRENT RATING: 1.0 A MAX

3.2 DIELECTRIC WITHSSTANDING VOLTAGE:
100 V(ac) FOR 1min

3.3 CONTACT RESISTANCE: 30 mΩ MAX.

3.4 INSULATION RESISTANCE: 100 MΩ MIN.

3.5 TOTAL MATING FORCE: 3.57 Kgf MAX.

3.6 TOTAL UNMATING FORCE: 1.0 Kgf MIN.

3.7 LIFE: 5,000 CYCLES

3.8 TEMPERATURE RANGE: -30˚C ~ +80˚C

ITEM NO.	DESCRIPTION	DRAWN	DATE
6	新增尺寸	Jack	071320
5	更新PCB LAYOUT尺寸	Jack	121119
4	更新樣式	Lan	041519
3	新增PCB LAYOUT尺寸	Jack	112317
2	更新端子長度	Jack	060617
1	新增PCB LAYOUT尺寸	Jack	020317

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS | MM

DRAWN BY: Jack Lu	DATE 07/13/20	MAT'L	
CHECKED BY: Jacky Chen	DATE 07/13/20	FINISH	
APPROVED BY: Tony Kao	DATE 07/13/20	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	CONNECTOR
MODLE	MICRO USB B TYPE 前插5.67 後貼 有柱 平口
DWG NO.	MRUSB-5B-ED8x-S347
PART NO.	MRUSB-5B-ED8x-S347
SIZE	A4
VER	R6