














P.C.B LAYOUT MOUNTING PATTERN

RoHS Compliant

SPECIFICATIONS

Electrical:

1.Current Rating: 1.0A / contact terminal
2.Voltage Rating: 30V DC
3.Contact Resistance: 50 milliohms Max
4.Dielectric Withstanding Voltage:
300 V AC AT Sec Level
5.Insulation Resistance: 100 MEGA ohms Min

Mechanical:

1.Connector Mate and Unmate Force
Mate force: 3.0 kgf (Max)
Unmate force: 0.7 kgf (Min)
2.Terminal Retention: 0.5 kgf (Min)

Material:

1.Housing:
High Temperature Thermal Plastics,
UL 94V-0 , LCP , Black
2.Contact: Phopshor Bronze
3.Shell: Brass

Finish:

1.Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls;
Nickel under plated overall
2.Shell: Tin under Plated surface layer

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新鍍層	Jack	102413
1	更新外殼鍍層	Jack	051513

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°
3RD. ANGEL'S
UNITS MM

		DATE
DRAWN BY:	Jack Lu	10/24/13
CHECKED BY:	Jacky Chen	10/24/13
APPROVED BY:	Tony Kao	10/24/13

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	MICRO 5PF SMT B 型 沉板1.6
SCALE	1 : 1	DWG NO.	MRUSB-5B-M6-S175 SIZE A4
SHEET NO.	1 of 1	PART NO.	MRUSB-5B-M6-S175 VER R2