


HDMI-D-19PL3xx-S165


外殼材質 :

Blank : Brass
I : Spcc


外殼電鍍材質 :


Blank : Nickel
G : Au







PCB LAYOUT









SPECIFICATIONS :

1.RATING: 40V , 0.3A

2. CONTACT RESISTANCE : 30 mΩ MAX

3. INSULATION RESISTANCE : 10 MΩ MIN

4. DIELECTNIC STRENGTH : 150V AC / 1 minute

5. DURABILITY : 5,000 cycles

6.TEMPERATURE RANGE : -25˚C ~ +85˚C

Material:

1.Housing: LCP

2.Contact: Phosphor Bronze

3.Shell: Brass / Spcc

Finish:

1.Contact: Plated Gold in Mating Area ;

Tin Plated on Solder Balls ;

Nickel under plated overall

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增PCB LAYOUT 尺寸	Jack	092220

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ± 0.2, Above 5 ~ 15 ± 0.3, Above 15 ~ 30 ± 0.4, Above 30 ~ 50 ± 0.5, Angle ± 0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu	DATE 09/22/20	MAT'L	
CHECKED BY: Jacky Chen	DATE 09/22/20	FINISH	
APPROVED BY: Tony Kao	DATE 09/22/20	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	CONNECTOR		
MODLE	HDMI D TYPE 公頭夾板式 板厚:1.2mm		
DWG NO.	HDMI-D-19PL3xx-S165	SIZE	A4
PART NO.	HDMI-D-19PL3xx-S165	VER	R1