



(Number of Conductors) N	X
(Pitch) P	1.00mm
(Total Pitch) Pt	X
(Total Length) L	X
(Film Length) IL	X
(Margin Width) M	X
(Total Width) W	X
(Strip Length) S1	X
(Strip Length) S2	X
(Stiffener) B1	X
(Stiffener) B2	X
(Slanting) A1	X
(Slanting) A2	X
(Terminal thickness) t	X
(Thickness) T	X

ITEM	DESCRIPTION	SPECIFICATION	REMARK
4	補強板 (Connecting)	0.225 (深藍色)	
3	上絕緣膠 (Top Insulation)	0.06 (白/印字white/printed)無鹵素皮膜	
2	下絕緣膠 (Under Insulation)	0.06 (白white)無鹵素皮膜	
1	導體 (Conductor)	0.035×0.65 (Tin Plating)	

**CONTACT** 建倚科技股份有限公司  
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:  
Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY: Jack Lu  
CHECKED BY: Jacky Chen  
APPROVED BY: Tony Kao

DATE: 11/27/15  
DATE: 11/27/15  
DATE: 11/27/15

MAT'L	TITLE	FFC CABLE
FINISH	MODLE	FFC CABLE
SCALE	DWG NO.	FC13-xxxx-S281
SHEET NO.	PART NO.	FC13-xxxx-S281

SIZE A4  
VER R