



P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATION

1. Rating : DC 30V 0.5A ;
2. Contact resistance : $\leq 30m\Omega$;
3. Insulation resistance : $\geq 100M\Omega$ (DC250V) ;
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles ◦

| | |
|-----------|---------------|
| MODEL NO. | PJ-D2016-S187 |
| SCHMATIC | |

| 4 | HOUSING | 1 | PA66(Black) | |
|-----|--------------|-----|-----------------|------------|
| 3 | CONTACT FOOT | 1 | Phosphor Bronze | Ag-Plating |
| 2 | CONTACT FOOT | 1 | Phosphor Bronze | Ag-Plating |
| 1 | CONTACT FOOT | 1 | Phosphor Bronze | Ag-Plating |
| NO. | DESCRIPTION | QTY | MATERIAL | PLATING |

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S UNITS MM

| | | | | |
|--------------|----------|-----------|----------|---------------|
| DRAWN BY: | DATE | MAT'L | TITLE | JACK |
| Jack Lu | 03/15/13 | | MODLE | PHONE JACK |
| CHECKED BY: | DATE | FINISH | SCALE | 1 : 1 |
| Jacky Chen | 03/15/13 | | DWG NO. | PJ-D2016-S187 |
| APPROVED BY: | DATE | SHEET NO. | PART NO. | PJ-D2016-S187 |
| Tony Kao | 03/15/13 | 1 of 1 | | |

| 1 | 更新尺寸 | Jack | 031513 |
|----------|-------------|-------|--------|
| ITEM NO. | DESCRIPTION | DRAWN | DATE |