





SPECIFICATIONS

Current rating : 2.0A AC , DC

Voltage rating : 250V AC , DC

Temperature rating : -25˚C ~ +85˚C

Insulation resistance : 100MΩ min.


Withstand voltage : 200V AC/minute


Contact resistance : 20mΩ/Max

Material:

Housing : LCP, UL94V-0

Contact : Phosphor Bronze,Tin over Nickel





P.C.B LAYOUT MOUNTING PATTERN

Circuits	Dimensions(mm)		
	A	B	C
02	2.00	4.80	8.00
03	4.00	6.80	10.00
04	6.00	8.80	12.00
05	8.00	10.80	14.00
06	10.00	12.80	16.00
07	12.00	14.80	18.00
08	14.00	16.80	20.00
09	16.00	18.80	22.00
10	18.00	20.80	24.00
11	20.00	22.80	26.00
12	22.00	24.80	28.00
13	24.00	26.80	30.00
14	26.00	28.80	32.00
15	28.00	30.80	34.00
16	30.00	32.80	36.00

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新樣式	Jack	112422
1	更新尺寸及SPEC	Jack	042219

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

		DATE
DRAWN BY:	Jack Lu	11/24/22
CHECKED BY:	Jacky Chen	11/24/22
APPROVED BY:	Tony Kao	11/24/22

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	WAFER P : 2.0mm SMT 180度
SCALE	1 : 1	DWG NO.	WF-2001VSxx-S304
SHEET NO.	1 of 1	PART NO.	WF-2001VSxx-S304

SIZE A4 | VER R2