



P.C.B LAYOUT

PART NO.	D1MA	D1MB	D1MC	D1MD
02	0.80	1.90	3.78	3.04
03	1.60	2.70	4.58	3.84
04	2.40	3.50	5.38	4.64
05	3.20	4.30	6.18	5.44
06	4.00	5.10	6.98	6.24
07	4.80	5.90	7.78	7.04
08	5.60	6.70	8.58	7.84
09	6.40	7.50	9.38	8.64
10	7.20	8.30	10.18	9.44
11	8.00	9.10	10.98	10.24
12	8.80	9.90	11.78	11.04
13	9.60	10.70	12.58	11.84
14	10.40	11.50	13.38	12.64
15	11.20	12.30	14.18	13.44
16	12.00	13.10	14.98	14.24
17	12.80	13.90	15.78	15.04
18	13.60	14.70	16.58	15.84
19	14.40	15.50	17.38	16.64
20	15.20	16.30	18.18	17.44

SPECIFICATIONS

- 1.Current rating : 0.7A AC , DC
 - 2.Voltage rating : 30V AC , DC
 - 3.Temperature rating : -25°C ~ +85°C
 - 4.Insulation resistance : 100MΩ min.
 - 5.Withstand voltage : 200V AC / minute
 - 6.Contact resistance : 20mΩ/Max
- Material:
- 1.Housing : LCP
 - 2.Contact : Brass,Gold Plated over all Nickel
 - 3.Fitting Nail : Brass,Gold Plated over all Nickel

ITEM NO.	DESCRIPTION	DRAWN	DATE
7	新增尺寸	Jack	040226
6	更新CAP樣式和尺寸	Jack	040126
5	新增尺寸	Jack	033126
4	更新圖面	Jack	021425
3	更新圖面	Jack	030122

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MATL	TITLE	CONNECTOR
Jack Lu	04/02/26			
CHECKED BY:	DATE	FINISH	MODLE	WAFER 0.8mm . SMT 180度
Jacky Chen	04/02/26	SCALE	1 : 1	DWG NO.
APPROVED BY:	DATE	SHEET NO.	PART NO.	WF-0800VSxx-S304
Tony Kao	04/02/26			