



SBC-240V4-31x-S271

鍍層厚度：

Blank : 1u"

2 : 15u"

3 : 30u"

PCB LAYOUT

SPECIFICATIONS

Electrical:

- 1.Rating: 3.0 A
- 2.Dielectric Withstand Voltage: 100V AC
- 3.Contact Resistance: 40 mΩ Max
- 4.Insulation Resistance: 100 MΩ Min

Material:

- 1.Housing: LCP,UL 94V-0
- 2.Contact: C1814
- 3.Shell: SUS

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°
3RD. ANGEL'S
UNITS MM

DRAWN BY:	DATE	MATL		TITLE	CONNECTOR
Jack Lu	01/12/23				
CHECKED BY:	DATE	FINISH		MODLE	USB 3.1 TYPE C 夾板母座
Jacky Chen	01/12/23				
APPROVED BY:	DATE	SCALE	1 : 1	DWG NO.	SBC-240V4-31x-S271
Tony Kao	01/12/23	SHEET NO.	1 of 1	PART NO.	SBC-240V4-31x-S271
					SIZE A4
					VER R2