












RECOMMEND P.C.B LAYOUT COMPONENT



RoHS Compliant

SUA-110E14Ax-x-S235

Shell Material :

Blank : Brass
I : SPCC

Color :

White : W
Black : B

SPECIFICATIONS

Electrical:

1.Voltage Current Rating: 1.5 A , 30V DC

2.Contact Resistance: 30 mΩ Max

3.Insulation Resistance: 1,000 MΩ Min

4.Dielectric Withstanding Voltage: 500 V AC

5.Mating Force: 3.57 Kg Max

6.Umating Force: 1.02 Kg Min

Material:

1.Housing: PBT

2.Contact: Brass

3.Shell: Brass / Spcc

Finish:

1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall

2.Shell: Nickel under Plated surface layer

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新樣式	Jack	050719
1	更新PCB LAYOUT	Jack	072618

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

		DATE
DRAWN BY:	Jack Lu	05/07/19
CHECKED BY:	Jacky Chen	05/07/19
APPROVED BY:	Tony Kao	05/07/19

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	USB AF SMT 無捲邊 沉板 H4.60mm
SCALE	1 : 1	DWG NO.	SUA-110E14Ax-x-S235
SHEET NO.	1 of 1	PART NO.	SUA-110E14Ax-x-S235

SIZE A4 | VER R2