





CIRCUIT DIAGRAM





P.C.B LAND PATTERN

SPECIFICATIONS

Rating	DC 12V 0.1A
Contact Resistance	100mΩ Max
Insulation Resistance	100MΩ Min
Operating Force	160 ±50gf
Life	10,000 cycles
Operation temperature range	-40˚C~85˚C

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CLIP	1	PHOSPHOR BRONZE	Ag plated
C	COVER	1	SUS	Ag plated
B	CASE	1	LCP	Black
A	SLIDER	1	PA46	Black

ITEM NO.	DESCRIPTION	DRAWN	DATE
5	新增Operation temperature range	Jack	121021
4	更新材質	Jack	091720
3	更新SLIDER的顏色	Jack	091620
2	更新圖面	Jack	060917
1	新增尺寸	Jack	052715

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 12/10/21	MAT'L	
CHECKED BY: Jacky Chen	DATE 12/10/21	FINISH	
APPROVED BY: Tony Kao	DATE 12/10/21	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH		
MODLE	SLIDE SWITCH		
DWG NO.	SS-B00-S246	SIZE	A4
PART NO.	SS-B00-S246	VER	R5