



P.C.B LAYOUT MOUNTING PATTERN



SUA-110V16Ax-x-S236

SHELL :

Blank : Brass

I : SPCC

COLOR :

Black: B

White : W

SPECIFICATIONS

Electrical:

- 1.Rating: 30V DC, 1.5A
- 2.Contact Resistance: 30 m Ω Max
- 3.Dielectric Withstanding Voltage: 500 V AC / 1 minute
- 4.Insulation Resistance: 1,000 M Ω Min

Material:

- 1.Housing: PBT
- 2.Contact: Brass
- 3.Shell: Brass / Spcc

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 09/11/20
DATE: 09/11/20
DATE: 09/11/20

MATL		TITLE	CONNECTOR
FINISH		MODLE	USB AF 180度直立式 H10.5, 無捲邊 腳距 2.2mm
SCALE	1 : 1	DWG NO.	SUA-110V16Ax-x-S236
SHEET NO.	1 of 1	PART NO.	SUA-110V16Ax-x-S236

SIZE
A4
VER
R