












CIRCUIT



P.C.B LAYOUT MOUNTING PATTERN







PS-6041N-xx-S088

COLOR OF LED

0	Without	1	Red
2	Green	3	Orange
4	Yellow	7	Blue
8	White		

COLOR OF LED

0	Without	1	Red
2	Green	3	Orange
4	Yellow	7	Blue
8	White		

SPECIFICATIONS:.

1.RATING : 0.1A , 30VDC

2.CONTACT RESISTANCE : 100 mΩ Max

3.INSULATION RESISTANCE : 100 MΩ min

4.DIELETRIC STRENGTH : 250 V AC / 1 MIN

5.OPERATING TEMPERTURE : -16˚C to 60˚C

6.OPERATING FORCE : 180 ± 500 gf

7. LIFE : 10,000 cycles .

8.Timing: Non-Shorting

9.Operation: Non-Lock TYPE

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新料號	Jack	022417

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ± 0.2; Above 5 ~ 15 ± 0.3; Above 15 ~ 30 ± 0.4; Above 30 ~ 50 ± 0.5; Angle ± 0.3˚

3RD. ANGEL'S | UNITS | MM

DRAWN BY: Jack Lu	DATE 02/24/17	MAT'L	
CHECKED BY: Jacky Chen	DATE 02/24/17	FINISH	
APPROVED BY: Tony Kao	DATE 02/24/17	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH		
MODLE	Push switch Non-Lock Type		
DWG NO.	PS-6041N-xx-S088	SIZE	A4
PART NO.	PS-6041N-xx-S088	VER	R1