



RoHS Compliant







P.C.B LAYOUT









SCHEMATIC

TS-H3-xx-C0xx-S065

COLOR OF LED

0	Without	1	Red
2	Green	3	Orange
4	Yellow	7	Blue
8	White		

CAP MODEL

S1	6.0mm Sq
S2	8.6mm Sq
S2A	8.6mm Sq
S3	11.0mm Sq
S3A	12.5mm Sq
S4	11.0mm Sq

CAP Color

0	Without	1	Red
2	Green	3	Yellow
4	Ivory	5	Gray
6	Black	8	White

SPECIFICATIONS

Rating	DC 20V 1mA
Contact Resistance	200 mΩ Max.
Insulation Resistance	100 MΩ Min.
Operating Temperature	-40˚C ~ +85˚C
Operating Force	125 ± 35gf
Operating Life (cycles)	300,000

ITEM NO.	DESCRIPTION	DRAWN	DATE

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ± 0.2; Above 5 ~ 15 ± 0.3; Above 15 ~ 30 ± 0.4; Above 30 ~ 50 ± 0.5; Angle ± 0.3˚

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 02/09/18	MAT'L	
CHECKED BY: Jacky Chen	DATE 02/09/18	FINISH	
APPROVED BY: Tony Kao	DATE 02/09/18	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	SWITCH
MODLE	TACT SWITCH W/I LED
DWG NO.	TS-H3-xx-C0xx-S065
PART NO.	TS-H3-xx-C0xx-S065
SIZE	A4
VER	R