








P.C.B LAYOUT
TOP VIEW

SCHEMATIC



Ø3.50mm 3 POLE PLUG

SPECIFICATION

- 1.Rating : DC 30V, 0.5A
- 2.Contact resistance : $\leq 30\text{m}\Omega$
- 3.Insulation resistance : $\geq 100\text{M}\Omega$
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-20N
- 6.life test : 5,000 cycles

9	COAT	1	IRON	Ni-Plating
8	COVER	1	PBT	
7	HOUSING	1	PBT	
6	AXIS SUPPORT	1	BRASS	Ni-Plating
5	CURVE PIECE	1	BRASS	Sn-Plating
4	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
3	CURVE PIECE	1	BRASS	Sn-Plating
2	SPRING PIECE	1	PHOSPHOR BRONZE	Sn-Plating
1	FLAT PIECE	1	BRASS	Sn-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MATL	TITLE	JACK
Jack Lu	09/24/19			
CHECKED BY:	DATE	FINISH	MODLE	3.5 PHONE JACK
Jacky Chen	09/24/19			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-D3055H-S124
Tony Kao	09/24/19	1 : 1		
		SHEET NO.	PART NO.	PJ-D3055H-S124
		1 of 1		
				SIZE A4
				VER R1