


SBC-160S6-20x-S412


鍍層厚度：

Blank : 1u"
2 : 15u"
3 : 30u"










A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	D+	B7	D-
A7	D-	B6	D+
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME



P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATIONS

Electrical:

1.Rating: 5.0A

1.Contact Resistance: 40 mΩ Max

2.Insulation Resistance: 100 MΩ Min

3.Dielectric Withstanding Voltage: 150V AC

Material:

1.Housing: LCP

2.Contact: C7025

3.Shell: SUS

Finish:

1.Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall

2.Shell: Nickel under Plated surface layer

ITEM NO.	DESCRIPTION	DRAWN	DATE
5	新增PIN定義	Jack	022023
4	更新圖面	Jack	081122
3	更新樣式	Jack	011221
2	更新圖面	Jack	010621
1	更新及新增尺寸	Jack	110520

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 02/20/23	MAT'L	
CHECKED BY: Jacky Chen	DATE 02/20/23	FINISH	
APPROVED BY: Tony Kao	DATE 02/20/23	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	CONNECTOR		
MODLE	TYPE CF TYPE CF 16P 全貼有柱有彈		
DWG NO.	SBC-160S6-20x-S412	SIZE	A4
PART NO.	SBC-160S6-20x-S412	VER	R5