











P.C.B LAYOUT MOUNTING PATTERN
(TOP VIEW)



RECOMMENDED PLUG

MODEL NO.	DC-021HT-x-S124
SCHEMATIC	
CENTER PIN	Ø2.0 mm
	Ø2.5 mm

SPECIFICATION

- Rating : DC 30V , 3.5A
- Contact resistance : $\leq 30\text{m}\Omega$
- Insulation resistance : $\geq 100\text{M}\Omega$
- Withstand voltage : 500VAC
- Insertion and extraction force : 3-20N
- life test : 5,000 cycles

⑥	PIN	1	Brass	Ni-Plating
⑤	FLAT FOOT	1	Brass	Ag-Plating
④	CURVE PIECE	1	Brass	Ag-Plating
③	SPRING PIECE	1	Phosphor Bronze	Ag-Plating
②	COVER	1	LCP	
①	HOUSING	1	LCP	
NO.	DESCRIPTION	QTY	MATERIAL	REMARK



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	10/01/21			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK
Jacky Chen	10/01/21			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-021HT-x-S124
Tony Kao	10/01/21	1 : 1		
		SHEET NO.	PART NO.	DC-021HT-x-S124
				SIZE A4
				VER R3