

RoHS Compliant


RJ45-41933-x-S118


鍍層厚度 :

Blank : 1u"
1 : 3u"
2 : 15u"
3 : 30u"
5 : 6u"











P.C.B LAYOUT
TOP VIEW





Recommended panel cutout.

NOTES:
ELECTRICAL:
1. VOLTAGE RATING :125 VAC RMS.
2. CURRENT RATING :1.5 AMP.
3. CONTACT RESISTANCE :30 MILLIOHMS MAX.
4. INSULATION RESISTANCE :1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH :1000 VDC RMS 60Hz, 1MIN.
6. OPERATING: 750 CYCLES MIN.
MATERIALS:
1. Housing: LCP BLACK
2. Cover: LCP BLACK
3. Shielding:Copper Alloy with Nickel Plated.
4. Contact: Phosphor Bronze gold Plating Over Nickel.
ENVIRONMENTAL:
1. STORAGE: -40° C TO +85° C.
2. OPERATION : -40° C TO +85° C.

ITEM NO.	DESCRIPTION	DRAWN	DATE

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 07/08/21	MAT'L	
CHECKED BY: Jacky Chen	DATE 07/08/21	FINISH	
APPROVED BY: Tony Kao	DATE 07/08/21	SCALE 1 : 1	SHEET NO. 2 of 1

TITLE	RJ45		
MODLE	RJ45		
DWG NO.	RJ45-41933-x-S118	SIZE	A4
PART NO.	RJ45-41933-x-S118	VER	R