




3 级插头接触点位置尺寸





5 级插头接触点位置尺寸





P.C.B LAYOUT














SPECIFICATION

1.Rating ：1.0A；

2.Contact resistance：≤100mΩ；

3.Insulation resistance：≥100MΩ；

4.Withstand voltage：500VAC ；

5.Insertion and extraction force：3-30N;

6.life test：5,000 cycles。

ITEM	NAME	Q'TY	DESCRIPTION
8	METAL BUSHING		C3604,GOLD FLASH
7	HOUSING	1	PA10T,COLOR BLACK.
6	TERMINAL 6#	1	STAIMLESS STEEL; NICKEL UNDER PLATING OVERALL,GOLD FLASH PLATING ON SOLDER AREA ;GOLD FLASH PLATING ON CONTACT AREA
5	TERMINAL 5#	1	
4	TERMINAL 4#	1	PHOSPHOR BRONZE; NICKEL UNDER PLATING OVERALL,GOLD FLASH PLATING ON SOLDER AREA ;GOLD FLASH PLATING ON CONTACT AREA
3	TERMINAL 3#	1	
2	TERMINAL 2#	1	
1	TERMINAL 1#	1	

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新材質	Jack	071122

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

DRAWN BY: Jack Lu	DATE 07/11/22	MAT'L	
CHECKED BY: Jacky Chen	DATE 07/11/22	FINISH	
APPROVED BY: Tony Kao	DATE 07/11/22	SCALE 1 : 1	SHEET NO. 1 of 1

TITLE	JACK		
MODLE	PHONE JACK		
DWG NO.	PJ-T53063-S214	SIZE	A4
PART NO.	PJ-T53063-S214	VER	R1