





| POLES | DIMENSIONS(mm) | |
|---|---|---|
| | A | B |
| 2 | 6.0 | 2.0 |
| 3 | 8.0 | 4.0 |
| 4 | 10.0 | 6.0 |
| 5 | 12.0 | 8.0 |
| 6 | 14.0 | 10.0 |
| 7 | 16.0 | 12.0 |
| 8 | 18.0 | 14.0 |
| 9 | 20.0 | 16.0 |
| 10 | 22.0 | 18.0 |
| 11 | 24..0 | 20.0 |
| 12 | 26.0 | 22.0 |
| 13 | 28.0 | 24.0 |
| 14 | 30.0 | 26.0 |
| 15 | 32.0 | 28.0 |
| 16 | 34.0 | 30.0 |




P.C.B LAYOUT MOUNTING PATTERN

## SPECIFICATIONS

Current rating : 2.0A AC , DC

Voltage rating : 250V AC , DC

Temperature rating : -25˚C ~ +85˚C

Insulation resistance : 1000MΩ min.

Withstand voltage : 800V AC/minute

Contact resistance : 10mΩ/Max

Material:

Housing : PA66

Contact : Brass,Tin over Nickel

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|---|---|---|---|
| 2 | 新增尺寸 | Jack | 081720 |
| 1 | 更新圖面 | Jack | 020218 |

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ±0.2; Above 5 ~ 15 ±0.3; Above 15 ~ 30 ±0.4; Above 30 ~ 50 ±0.5; Angle ±0.3°

3RD. ANGEL'S | UNITS MM

| | | DATE |
|---|---|---|
| DRAWN BY: | Jack Lu | 08/17/20 |
| CHECKED BY: | Jacky Chen | 08/17/20 |
| APPROVED BY: | Tony Kao | 08/17/20 |

| | | | |
|---|---|---|---|
| MAT'L | | TITLE | CONNECTOR |
| FINISH | | MODLE | WAFER P : 2.0mm DIP 180度 |
| SCALE | 1 : 1 | DWG NO. | WF-2001VDxx-S304 |
| SHEET NO. | 1 of 1 | PART NO. | WF-2001VDxx-S304 |

SIZE A4 | VER R2