



FH-C1A2-32xxx-S304

PIN數

	L1	L2	L3	L4
A	4.30	5.90	2.60	3.00

SPECIFICATIONS:

- 1.Current Rating : 1.0 A
- 2.Insulation Resistance : 1,000MΩ Min
- 3.Contact Resistance : 20mΩ Max
- 4.Operation Temperature : -40°C to +105°C

MATERIALS:

- 1.Insulator : PA6T
- 2.Contact : Brass
- 3.Contact Plating : Gold over Nickel

P. C. B. LaYout

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 11/22/21
DATE: 11/22/21
DATE: 11/22/21

MATL	TITLE	Female Header
FINISH	MODLE	1.27 Female Header DIP
SCALE	1 : 1	DWG NO. FH-C1A2-32xxx-S304
SHEET NO.	1 of 1	PART NO. FH-C1A2-32xxx-S304

SIZE	A4
VER	R