










P.C.B LAYOUT
TOP VIEW



ø3.50mm 4 POLE PLUG

SCHEMATIC

PJ-S3246



SPECIFICATION

- 1.Rating : DC 30V, 1.0A
- 2.Contact resistance : $\leq 30\text{m}\Omega$
- 3.Insulation resistance : $\geq 100\text{M}\Omega$
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-30N
- 6.life test : 5,000 cycles

6	HOUSING	1	PA9T	
5	5# CONTACT FOOT	1	SUS	Au-Plating
4	4# CONTACT FOOT	1	SUS	Au-Plating
3	3# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
2	2# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
1	1# CONTACT FOOT	1	SUS	Au-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING
DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	11/03/23	FINISH	MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-S3246-S124
Jacky Chen	11/03/23	1 : 1	PART NO.	PJ-S3246-S124
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	11/03/23			



建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3

3RD.
ANGEL'S



UNITS

MM

1	新增 P.C.B LAYOUT 尺寸	Jack	110323
ITEM NO.	DESCRIPTION	DRAWN	DATE