



**SPECIFICATIONS**

Rating	100mA , 12V DC
Insulation Resistance	50MΩ Min.
Dielectric Withstanding Voltage	AC 250 V(50Hz)1min
Contact Resistance	100mΩ Max.
Operating Force	200 ± 70gf
Operating Life	10,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
E	TERMINAL	4	PHOSPHOR BRONZE	Ag plated
D	CLIP	1	PHOSPHOR BRONZE	Ag plated
C	COVER	1	SUS	
B	BASE	1	LCP	Black
A	SLIDER	1	PA46	Black

**CONTACT** 建倚科技股份有限公司  
**CONTACT TECHNOLOGY CORP.**

TOLERANCE UNLESS OTHERWISE STATED :  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	05/08/24		MODLE	SMT 三段式 SLIDE SWITCH
CHECKED BY:	DATE	SCALE	DWG NO.	SS-C70-S246
Jacky Chen	05/08/24	1 : 1	PART NO.	SS-C70-S246
APPROVED BY:	DATE	SHEET NO.		SIZE
Tony Kao	05/08/24	1 of 1		A4
				VER
				R1

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新圖面	Jack	050824