



RECOMMENDED  
SOLDER PAD LAYOUT

SPECIFICATION

1. Rating : DC 12V 1.0A
2. Contact resistance :  $\leq 50m\Omega$
3. Insulation resistance :  $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

\*MATERIAL

- TERMINAL 1 : PHOSPHOR BRONZE
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : PHOSPHOR BRONZE
- TERMINAL 10 : BRASS
- TERMINAL 11 : PHOSPHOR BRONZE
- HOUSING : PA6T

MODEL NO.	PJ-2875D	PJ-2874AD	PJ-2874BD	PJ-2873D	PJ-2873AD
SCHEMATIC					

**CONTACT** 建倚科技股份有限公司  
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :  
Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu  
CHECKED BY: Jacky Chen  
APPROVED BY: Tony Kao

DATE: 11/04/15  
DATE: 11/04/15  
DATE: 11/04/15

MAT'L	TITLE	JACK
FINISH	MODLE	PHONE JACK
SCALE	1 : 1	DWG NO. PJ-287xD
SHEET NO.	1 of 1	PART NO. PJ-287xD

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增SPEC	Jack	110415