


RECOMMENDED SOLDER PAD LAYOUT

SPECIFICATION

1. Rating : DC 12V 1.0A
2. Contact resistance : $\leq 50m\Omega$
3. Insulation resistance : $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

*** MATERIAL**

- TERMINAL 1 : PHOSPHOR BRONZE
- TERMINAL 2 : BRASS
- TERMINAL 3 : BRASS
- TERMINAL 4 : PHOSPHOR BRONZE
- TERMINAL 10 : PHOSPHOR BRONZE
- TERMINAL 11 : PHOSPHOR BRONZE
- HOUSING : PA6T



MODEL NO.	PJ-297D	PJ-2975AD	PJ-2975BD	PJ-2974D
SCHEMATIC				

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	11/04/15		MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-297xD
Jacky Chen	11/04/15	1 : 1	PART NO.	PJ-297xD
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	11/04/15			

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增SPEC	Jack	110415