



SPECIFICATIONS

- 1.RATING: DC 5.0V,1.0mA ; DC 3.0V,1.0uA
- 2.CONTACT RESISTANCE: 3Ω Max.
- 3.INSULATION RESISTANCE: 100MΩ Min.
- 4.WITHSTAND VOLTAGE: AC 100V/ MINUTE.
- 5.OPERATING FORCE: 35gf Max.
- 6.OPERATING LIFE CYCLE: 50,000 CYCLES.

NO	PART NAME	QTY	MATERIAL	REMARK
6	SPACER	1	PA46	
5	TERMINAL	1	PBS	Ag plating
4	HOUSING	1	LCP	
3	CONTACT FORM	1	PBS	Ag plating
2	COVER	1	SUS	
1	STEM	1	PA46	

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2, Above 5 ~ 15 ±0.3, Above 15 ~ 30 ±0.4, Above 30 ~ 50 ±0.5

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	03/18/22	FINISH	MODLE	DETECTOR SWITCH(PUSH OFF TYPE)
CHECKED BY:	DATE	SCALE	DWG NO.	DS-C52E-S138
Jacky Chen	03/18/22	SHEET NO.	PART NO.	DS-C52E-S138
APPROVED BY:	DATE			SIZE A4
Tony Kao	03/18/22			VER R1

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增ON和OFF和TRAVEL標示	Jack	031822