


1. Functional spec.	
1.1 Rated Voltage	AC125V 3A / AC250V 1.5A
1.2 Contact Resistance	$\leq 100\text{m}\Omega$
1.3 Operating Force	130 ± 30 gf
1.4 Free Position	7.35 ± 0.2 mm
1.5 Operating Position	7.0 ± 0.2 mm
2. Reliable Rating	
2.1 Mechanical Life	1000,000 CYCLES
2.2 Electrical Life	10,000 / 1,000,000 CYCLES
2.3 Insulation Resistance	$\geq 100\text{M}\Omega$ DC500V
2.4 Withstand Voltage	AC500V 1 minute
2.5 Soldering Temper	250°C Max 3 Sec.
2.6 Operating Temper	-25°C $\sim$ +65°C
2.7 Ambient Humidity Used	<85%RH

SCHEMATIC



				 建倚科技股份有限公司 CONTACT TECHNOLOGY CORP.	DRAWN BY: DATE		MAT'L	TITLE	SWITCH		
					Jack Lu	12/09/15					
					CHECKED BY: DATE		FINISH	MODLE	MICRO SWITCH		
7	3	更新Rated Voltage	Jack		120915	Jacky Chen				12/09/15	
	2	圖面標示更新	Jack		031714	TOLERANCE UNLESS OTHERWISE STATED : Up to 5 ± 0.2 Above 5 ~ 15 ± 0.3 Above 15 ~ 30 ± 0.4 Above 30 ~ 50 ± 0.5 Angle $\pm 0.3'$ 3RD. ANGEL'S  UNITS MM		SCALE	1 : 1	DWG NO.	DM3-00P
	1	圖面更新	FrankWu	120211	A4						
	ITEM NO. DESCRIPTION		DRAWN	DATE	VER						
	A	B	C	D	E	F	G	H	I	J	R2