


P.C.B MOUNTING PATTERN

SPECIFICATIONS

- 1. Rating : DC 30V 0.1A
- 2. Circuit : 2P2T
- 3. Timing : Non-Shorting
- 4. Operating force : 250 ± 100gf
- 5. Life test : 10,000 cycles

NOTE:

- 1. PS-D12L-S191: SELF-LOCK
- 2. PS-D12NL-S191: NON-LOCK



SCHEMATIC

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
6	CONTACT(CLIP)	2	PHOSPHOR BRONZE	Ag-Plated
5	SPRING	1	SUS	
4	TERMINAL	6	BRASS	Ag-Plated
3	CASE	1	PBT	BLACK
2	COVER	1	POM	WHITE
1	KNOB	1	POM	BLUE

ITEM NO.	DESCRIPTION	DRAWN	DATE
5	更新圖面	Jack	041322
4	更新KNOB顏色	Jack	032322
3	更新COPING CASE材質	Jack	032222
2	新增SPEC	Jack	102315
1	新增PIN編號	Jack	101215

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MATL	TITLE	SWITCH
Jack Lu	04/13/22		MODLE	PUSH SWITCH
CHECKED BY:	DATE	FINISH	SCALE	1 : 1
Jacky Chen	04/13/22		DWG NO.	PS-D12x-S191
APPROVED BY:	DATE	SHEET NO.	PART NO.	PS-D12x-S191
Tony Kao	04/13/22	1 of 1		

SIZE A4
VER R5