



PCB LAYOUT MOUNTING PATTERN

**SPECIFICATIONS**

Electrical:

- 1.Voltage Rating : 125 VAC RMS
- 2.Current Rating : 1.5 AMP
- 3.Contact Resistance : 30 mΩ MAX
- 4.Insulation Resistance : 500 MΩ MIN. @500 VDC
- 5.Dielectric Strength : 1,000 VAC RMS 50 HZ 1 MIN

Material:

- 1.Housing : PBT/PA46 ,UL94V-0
- 2.Contact : Phosphor Bronze , Gold Plating over Nickel
- 3.Shield : Copper Alloy, Nickel Plated

Environmental:

- 1.Operation Temperature : -40°C ~ +85°C
- 2.Storage Temperature : -40°C ~ +85°C

**CONTACT** 建倚科技股份有限公司  
**CONTACT TECHNOLOGY CORP.**

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	RJ45
Jack Lu	10/12/20			
CHECKED BY:	DATE	FINISH	MODLE	RJ45
Jacky Chen	10/12/20			
APPROVED BY:	DATE	SCALE	DWG NO.	RJ45-52T8811E-S307
Tony Kao	10/12/20	1 : 1	PART NO.	RJ45-52T8811E-S307
		SHEET NO.	1 of 1	
				SIZE A4
				VER R1

1	新增尺寸	Jack	101220
ITEM NO.	DESCRIPTION	DRAWN	DATE