


MODEL No	L (mm)
TS-A01V	3.15
TS-A01VA	3.85



CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	DC 12V , 50mA
Contact Resistance	100mΩ Max.
Travel	0.25 ± 0.1mm
Operating Force	0 100 ± 30gf 1 130 ± 30gf 2 180 ± 30gf 3 250 ± 50gf
Operating Life (cycles)	100,000

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
E	TERMINAL	2	BRASS	Ag plated
D	CONTACT	1	SUS	Ag plated
C	COVER	1	SUS	Ni plated
B	CASE	1	PA6T	
A	STEM	1	PA6T	

ITEM NO.	DESCRIPTION	DRAWN	DATE
8	更新尺寸	Jack	051326
7	新增材質表	Jack	080320
6	更新樣式	Jack	041519
5	更新PIN腳樣式	Jack	011119

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MATL	TITLE	SWITCH
Jack Lu	05/13/26	FINISH	MODLE	TACT SWITCH
CHECKED BY:	DATE	SCALE	DWG NO.	TS-A01Vx-x-S126
Jacky Chen	05/13/26	1 : 1	PART NO.	TS-A01Vx-x-S126
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	05/13/26			

SIZE
A4
VER
R8