


P.C.B LAND PATTERN

SPECIFICATIONS

Rating	50mA 12V DC
Insulation Resistance	100MΩ Min.
Dielectric Withstanding Voltage	AC 250 V
Contact Resistance	100mΩ Max.
Operating Force	2 160 ± 50gf 3 260 ± 50gf
Operating Life(cycles)	70,000



CIRCUIT DIAGRAM

D	FILM	1		
C	CONTACT	1	SUS	Ag plated
B	BASE	1	LCP(Black)	
A	THERMINAL	4	PHOSPHOR BRONZE	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 - 15 ±0.3
 Above 15 - 30 ±0.4
 Above 30 - 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	05/07/20		MODLE	TACT SWITCH
CHECKED BY:	DATE	FINISH	SCALE	1 : 1
Jacky Chen	05/07/20		DWG NO.	TS-A96-x-S410
APPROVED BY:	DATE	SHEET NO.	PART NO.	TS-A96-x-S410
Tony Kao	05/07/20	1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE