


P.C.B LAND PATTERN



CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	50mA 12V DC	
Insulation Resistance	100MΩ Min.	
Dielectric Withstanding Voltage	AC 250 V	
Contact Resistance	100mΩ Max.	
Operating Force	2 160 ± 50gf	3 260 ± 50gf
Operating Life(cycles)	100,000	50,000

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
D	FILM	1		
C	CONTACT	1	SUS	Ag plated
B	BASE	1	LCP(Black)	
A	THERMINAL	4	PHOSPHOR BRONZE	

**CONTACT** 建倚科技股份有限公司  
**CONTACT TECHNOLOGY CORP.**

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 - 15 ±0.3  
 Above 15 - 30 ±0.4  
 Above 30 - 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	05/21/20		MODLE	TACT SWITCH
CHECKED BY:	DATE	SCALE	DWG NO.	TS-A96U-x-S410
Jacky Chen	05/21/20	1 : 1	PART NO.	TS-A96U-x-S410
APPROVED BY:	DATE	SHEET NO.		
Tony Kao	05/21/20	1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE