



SPECIFICATION

- Contact resistance : $\leq 30m\Omega$
- Insulation resistance : $\geq 100M\Omega$
- Withstand voltage : 500VAC
- Insertion and extraction force : 6-20N
- life test : 5,000 cycles
- Waterproof Level: IPx7

⑩	OVAL RING	----	1	SILICONE	
⑨	BOND	----	1	EPOXY	----
⑧	TERMINAL	----	2	C2680	
⑦	TIP SPRING-2	⑤	1	Ti-Cu	Gold PLATED ,Nickel Underplate
⑥	RING SPRING-2	④	1	Ti-Cu	
⑤	RING SPRING-1	③	1	Ti-Cu	
④	TIP SPRING-1	②	1	Ti-Cu	
③	EARTH SPRING	①	1	Ti-Cu	
②	COVER	----	1	PA9T	
①	HOUSING	----	1	PA9T	
ITEM	PART NAME	TERMINAL	QTY	MATERIAL	REMARK

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu 04/12/19
 CHECKED BY: Jacky Chen 04/12/19
 APPROVED BY: Tony Kao 04/12/19

DATE: 04/12/19
 DATE: 04/12/19
 DATE: 04/12/19

MAT'L: JACK
 FINISH: 3.5mm PHONE JACK 防水型
 SCALE: 1 : 1
 DWG NO.: PJ-WP35383E-S404
 SHEET NO.: 1 of 1
 PART NO.: PJ-WP35383E-S404

SIZE: A4
 VER: R

ITEM NO.	DESCRIPTION	DRAWN	DATE