


CIRCUIT DIAGRAM



PCB LAYOUT

SPECIFICATIONS

Rating	DC 12V 50mA.			
Contact Resistance	100 m Ω Max.			
Operating Force	2	180 ± 50gf	3	260 ± 50gf
Operating Life (cycles)	100,000			

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
8	HOUSING	1	PA66	
7	TAPE	1	SILICON RUBBER	
6	FILM	1	GATHERS THE IMIDE	
5	PLUG	1	PA66	
4	CONTACT	1	SUS	Ag plated
3	FRAME	1	PPS	Ag plated
2	PLATE LAYER	1	CYANIDE	
1	TERMINAL	1	BRASS	Ag plated
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

CONTACT 建倚科技股份有限公司
CONTACT TECHNOLOGY CORP.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	SIZE
Jack Lu	08/28/18		SWITCH	A4
CHECKED BY:	DATE	FINISH	MODLE	VER
Jacky Chen	08/28/18		防水 TACT SWITCH	R
APPROVED BY:	DATE	SCALE	DWG NO.	
Tony Kao	08/28/18	1 : 1	TS-A62W-x-S138	
		SHEET NO.	PART NO.	
		1 of 1	TS-A62W-x-S138	

ITEM NO.	DESCRIPTION	DRAWN	DATE